

StealthTouch-M5 Touchcomputer

compact, fanless, and versatile

StealthTouch-M5 is a 15" All-in-one touchcomputer powered by Intel Pentium-M technology. Its versatile design allows you to customize the M5 to meet your application requirements and budget. The M5's versatility makes it an ideal choice for applications in food service, retail, manufacturing, healthcare, and self-service kiosk.

When configured as fanless and diskless thin client, the M5 will reduce grease and dust intakes. It also has the power to run demanding applications in Windows XP or Vista.

M5's benefits:

- + Rugged and slim design.
- + Choice of Resistive touch, Intellitouch, or InfraRed.
- + Blazing network, 10/100/1000BaseT. Wireless (WiFi) optional.
- + 4 Serial, 6 USB ports.
- + PoweredUSB to power up receipt printer, credit card terminal.
- + Integrated magnetic stripe reader and biometric fingerprint reader.
- + 2nd display port for advertisement on LCD or Plasma display.



Specifications

| | |
|------------------------|--|
| Display | 15" LCD, Active matrix TFT, 1024x768 |
| Touchscreen Option | Resistive, Intellitouch SAW, InfraRed |
| Processor | Intel Celeron-M 1GHz, Pentium-M 1.6GHz |
| Memory | 256MB, upto 1GB DDR2 |
| Video Memory | upto 128MB (shared) |
| Storage | Hard Drive, Solid-state Disk, or Compact Flash |
| CD/DVD | Internal (optional) |
| Operating System | XP Prof, WePOS, XP embedded, CE.NET, Linux |
| Network/Ethernet | 10/100/1000 BaseT |
| WiFi (wireless) | RF 802.11 (optional) |
| Serial Port | 4 |
| USB 2.0 | 6 : 4 Standard, 2 powered +12V, 1 powered +24V |
| Parallel Port | 1 |
| Cashdrawer Port | 2 (Epson emulation, 24V) |
| CF Slot | 1 (optional) |
| Speakers | 2 Watts, Stereo (optional) |
| Mounting Options | Wall or Pole mount, VESA 75mm |
| Security Lock | Bolted (4mm screw), or Kensington MicroSaver |
| Bezel Color | Dark grey |
| Dimensions (with Base) | Width: 14.63" (380mm) Height: 14.37" (373mm) Depth: 10.37" (269mm), Wallmount: 3.3" (85mm) |
| Weight | 22 lbs / 10 kgs (Wallmount: 10 lbs / 4.6 kgs) |
| Operating Temperature | 0° C to 40° C |
| Operating Humidity | 20% to 80% |
| Power Supply | External, 120W, AC 100-240V |
| Agency Approvals | FCC A, CE, UL |
| Add-ons | Magnetic stripe or Barcode slot reader Fingerprint /Biometric reader (DigitalPersona) Rear customer display or 10" LCD Barcode scanner (omni-directional) |



VESA mount

Barcode scanner



Rear display



Dual view

Product by



PioneerPOS, INC.

www.pioneerpos.com

888.468.9757